

ROOFING COMPONENT APPROVAL

Category: Roofing
Sub-Category: Underlayment
Material: Polypropylene

SCOPE:

This acceptance is for **Titanium® UDL25, Titanium® UDL30, Titanium® UDL50, Titanium® X30, Titanium® PSU30, RhinoRoof® U10, RhinoRoof® U20, RhinoRoof® Granulated, RhinoRoof® Metal, Tri-Built, ABC Pro Guard 20, and SRS TopShield TS20 Underlayments** as described in this Notice of Acceptance, for use with approved prepared roof assemblies where ASTM D226 Type II (Titanium® X30, Titanium® UDL30, Titanium® UDL50, RhinoRoof® U10, RhinoRoof® U20, Titanium® UDL25, ABC Pro Guard 20, Tri-Built, SRS TopShield TS20) or ASTM D1970 (RhinoRoof® Granulated, RhinoRoof® Metal, and Titanium® PSU30 only) underlayment is specified and installed with prescribed approved fasteners and fastener densities. Designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code

PRODUCT DESCRIPTION:

| <u>Product</u> | <u>Dimensions</u> | <u>Test Specification</u> | <u>Product Description</u> |
|---|-------------------|---------------------------|---|
| Titanium UDL25 <i>Manufacturing Location #1</i> | 48" x 250' rolls | ASTM D226 Type I & II | Woven synthetic polymer underlayment with two sides coated with UV protected and slip resistant polymer stabilized polypropylene on both sides. |
| Titanium® UDL-30 <i>Manufacturing Location #1</i> | 48" x 250' rolls | ASTM D226 Type I & II | Woven synthetic polymer underlayment with two sides coated with UV protected and slip resistant polymer stabilized polypropylene on both sides. |
| Titanium® UDL-50 <i>Manufacturing Location #1</i> | 48" x 250' rolls | ASTM D226 Type I & II | Woven synthetic polymer underlayment with two sides coated with UV protected and slip resistant polymer stabilized polypropylene on both sides. |
| RhinoRoof U20 <i>Manufacturing Location #1,2</i> | 42" x 286' rolls | ASTM D226 Type I and II | Woven synthetic polymer underlayment with two sides coated with UV protected and slip resistant polymer stabilized polypropylene on both sides. |
| RhinoRoof U10 <i>Manufacturing Location #1,2</i> | 42" x 286' rolls | ASTM D226 Type I & II | Woven synthetic polymer underlayment with two sides coated with UV protected and slip resistant polymer stabilized polypropylene on both sides. |
| RhinoRoof Granulated <i>Manufacturing Location #3,4</i> | 36"x65' rolls | ASTM D1970 | SBS self-adhering modified asphalt underlayment sheet material with a surfacing of opaque granules; for use as an underlayment in sloped roof assemblies. |
| RhinoRoof Metal <i>Manufacturing Location #3</i> | 36"x71.3" rolls | ASTM D1970 | SBS self-adhering asphalt sheet material with a film facer; for use as an underlayment in sloped roof assemblies |



NOA No.: 20-0818.08
 Expiration Date: 08/08/23
 Approval Date: 02/25/21
 Page 2 of 6